

# ***Installation and Maintenance Tiger Fish Clamp on Outrigger Holders***

## **Installation of Model # 88965 - 88966 - 88967**

\*Be sure that your t-top is constructed of schedule aluminum pipe and the proper mounting surface to provide a strong mounting surface for your new clamp-on outrigger holders.

\*We manufacture these units in three sizes to fit schedule aluminum pipe of marine t-tops and tuna or marlin towers.

\*Do not install on stainless or aluminum tube as this will void our manufacturer warrant. Stainless or aluminum tube will not support the structure, additionally the clamps are sized specifically for schedule aluminum pipe.

1. Find the location you wish to install your new clamp on outrigger holders.
2. Drill a 1/4 inch hole on the inside of the pipe, this will correspond to the 1/4 inch pin on the inside of the clamp. Position the hole along the center line on the pipe.
3. Remove the PVC liner on the inside of the clamp to expose the adjusting screw. Loosen the screw and select the angle you desire for your outrigger. Retighten the screw with locktite blue and replace the pvc isolator pad.
4. Position the outrigger holder with the handle facing the bottom of your boat for easy deployment.
5. Position the back half of the clamp with the pin in the previously drilled 1/4 inch hole.
6. Bolt the clamp sections together using lock tite blue.

Your installation is now complete.

**Maintenance:** Wash with Fresh Water After Each Use.

**Warranty:** Your New Tiger Fish Top Mount holder was inspected and tested before leaving the factory. We warranty this product to be free from defects in materials and workmanship under normal use and service for a period of One Year from date of purchase.



# ***Installation and Maintenance Tiger Fish Clamp On Outrigger Holders***

Directions for Use: Model #88965 - 88966 - 88967

1. This unit is a spring loaded mechanism.
  2. To move your outriggers from the resting position,
    - A. Turn the t-handle counter clock wise approximately three turns, this will release the inner pin set.
    - B. Pull the t-handle down and move your outriggers to the fishing position.
    - C. Once your have positioned your outriggers, release the t-handle the pins will set back into place.
    - D. Turn the t-handle clockwise until t-handle is tightened.
- Always confirm that your t-handle is completely tightened, so that your manufactures warranty is not voided.

**TIGHT LINES AND GOOD FISHING**

For Prompt Repair and Service: Please return your Tigress Product with dated proof of purchase to Tigress Outriggers & Gear at the address below:

2516 SW 4th Ave.  
Ft. Lauderdale, FL 33315  
(954) 462-0917

## ***Warranty Registration Card***

Please complete and Return with copy of receipt, so that we may add you to our Owner Registration Files:

Name: \_\_\_\_\_

Address: \_\_\_\_\_

City: \_\_\_\_\_ State: \_\_\_\_\_ Zip: \_\_\_\_\_

Date Purchased: \_\_\_\_\_

Product #: \_\_\_\_\_

Product Description: \_\_\_\_\_

Mail To: Tigress Outriggers & Gear  
2516 South West 4th Avenue  
Fort Lauderdale, Florida 33315  
Attn: Warranty Department

